

Assembly Equipment

Crimpers.....	3-4
Cut Off and Assembly Tools.....	3-6
Cut Off Machines	3-1 — 3-2
Cut Off Tools.....	3-3
Tube Benders	3-5

If you can't find it, your local Parker distributor can!

Just because it's not in our catalog doesn't mean you can't get it. To find exactly what you need, contact your local Parker distributor today. We can often provide 24-hour delivery direct from our factories to over 12,000 distribution locations worldwide. Our business is keeping you on the move.

- Features:**
- Portable saw for cutting on the job
 - Unique clamp system spreads hose as it cuts to prevent blade binding
 - Cuts multi-braided wire reinforced hose including 4 spiral construction up to 1-1/4" I.D.
- Dimensions:** 16" wide x 12" long x 19" high

HOSE ASSEMBLY

HOSE CUT-OFF MACHINE - KARRYKUT

3



Part No.	Description	Individual Part No.
631075		
+	Power saw with 115 volt (13 amp) universal AC motor	631140
+	Universal clamp attachment (can be used with any portable power saw unit have a 5/8" arbor, 8" blade capacity)	631076
+	Cutting Blade (8" with 5/8" arbor size)	580661

- Features:**
- Designed for heavy duty use
 - Cuts multi-braided wire reinforced hose including 6 spiral construction up to 2" I.D.
- Dimensions:** 22" wide x 42" long x 24" high

HOSE ASSEMBLY

HOSE CUT-OFF MACHINE



239



339

Part No.	Description	Individual Part No.
239		
339		
+	Hose Cut-Off Machine with 230V single phase motor	
+	Hose Cut-Off Machine with 3 HP motor 230V, 3 phase, 60 cycle	
+	Scallop Cutting Blade (10" with 3/4" arbor size)	24248
Optional	Smooth Cutting Blade	15960

- Features:**
- For quick, easy cutting of spiral reinforced hose up to 1-1/4" I.D.
 - Moving parts shielded by guards
- Dimensions:** 26" wide x 13" long x 22" high

HOSE ASSEMBLY

HOSE CUT-OFF MACHINE



Part No.	Description	Individual Part No.
332T-115V		
+	Hose Cut-Off Machine with 1-1/2 HP, 3450 RPM, 115/230V single phase electric motor wired for 115V	
+	Smooth Cutting Blade (8" with 5/8" arbor size)	580661
Optional	Scallop Cutting Blade	24398

- Features:**
- Portable tool for efficient cutting of hose
 - Can be positioned onto a flat surface by clamps or by locking it in a vise, properly align the hose in a radius and cut it with a hacksaw
- Dimensions:** 6" wide x 18" long x 6" high

HOSE ASSEMBLY

HOSE CUT-OFF TOOL - HANDYKUT

3



Part No.	Description
871522	Handykut hose cut-off tool

- Features:**
- Small in size and easy to use
 - Quick cutting of textile reinforced hose
 - Ruggedly built for years of trouble-free service
- Dimensions:** 15" long

HOSE ASSEMBLY

HOSE CUT-OFF TOOL



Part No.	Description
316	Hose cut-off tool

- Features:**
- Designed for quick, easy cutting of textile reinforced hose
 - Squarely cuts Push-Lok hose in sizes 1/4" through 3/4" I.D.
- Dimensions:** 8" long

HOSE ASSEMBLY

HOSE CUT-OFF TOOL



Part No.	Description
TH11-1	Hose cut-off tool

Features:

- Compact bench mount design
- Engineered for optimal durability
- All in one crimper and power unit design
- For use with 43 and 81 Series fittings

Specifications:

- Dimensions: 26" wide, 20" deep, 25" high
- Weight: 275 lbs (with power unit)
- Rating: 30 ton force @ 3,000 psi maximum
- Full Cycle Time: 20 seconds
- Hydraulic Fluid: AW32 oil
- Note: Includes a 115/230 volt, 1 phase, 60 hertz power unit wired for 115V. This unit comes with a 20 AMP male plug and must be run on a dedicated 20 AMP circuit.

HOSE ASSEMBLY

PARKRIMP 1



Part No. 80C-101	Description
+	Parkrimp 1 crimper with 115/230 volt, 1 phase, 60 Hz power unit wired for 115V
+	Silver die ring
+	Black die ring
+	43 Series dies (sizes 1/4", 3/8", 1/2", 3/4" and 1")

General Description: These are individual benders for eight inch tube sizes (1/8", 3/16", 1/4", 5/16", 3/8", 1/2", 5/8", 3/4"). All of these benders will bend copper, aluminum, annealed steel and stainless steel. These can be used in hands or mounted in a bench vise.

EQUIPMENT

MEDIUM DUTY INCH HAND TUBE BENDERS



3

Part No.	Size	Tube O.D. (in.)	Radius to Tube Centerline	Min. Wall Without Flattening	Recommended Max. Wall Thickness (in.)	
					Copper, Aluminum	Steel, Stainless Steel
2-2829S	2	1/8	7/16	0.012	Any	0.032
3-2829S	3	3/16	9/16	0.020	Any	0.032
4-2829S	4	1/4	9/16	0.028	Any	0.083
6-2829S	6	3/8	15/16	0.032	Any	0.083
8-2829S	8	1/2	1 1/2	0.042	Any	0.083

- Features:** • Combined hose cutter and toggle action press that cuts and assembles Parker Push-Lok in sizes 1/4" through 3/4" I.D.
- Dimensions:** 16" long

HOSE ASSEMBLY

PUSH-LOK CUT-OFF & ASSEMBLY TOOL



Part No.
881540

Description

+

Push-Lok cut-off & assembly tool